

Line matching transformer. 75Ω 1:1:1


B5077

Provisional Data Sheet

Features

- 16mm Seated height
- Resin encapsulated
- Tested to 500V DC isolation
- 8Mbps interface
- Flammability to UL94 V0

Dimensions



Dimensions in mm (inches)

Recommended PCB hole size 1.0mm Ø

Pin grid and box geometric centres coincide within a tolerance circle of 1.0mm

Tolerances ±0.1mm

Technical Data

Parameter	Conditions	Value
Inductance pins 5-8	10 kHz	15 mH
Leakage Inductance pins 1-3	100 kHz	3 µH typical
Ratio Pins 5-8 : 1-2 + 3-4		1 : 1 + 1
Isolation voltage	DC	500 V
Operating Range	Ambient temperature	
Functional		-10°C to 70°C
Storage		-40°C to 125°C

Best
Windings Ltd

www.bestwindings.co.uk

*Best Windings Ltd, Viking Works,
Bucklesham Road, Kirton, Ipswich,
Suffolk, England. IP10 ONX*

E-Mail: sales@bestwindings.co.uk

Tel: + 44 (0) 1394 448 424

Fax: + 44 (0) 1394 448 430

©The product numbers used are the trademarks of Best Windings Ltd
©1996-2007 Best Windings Ltd. Reproduction Prohibited

November 2007