

# Line Txfr 600 : 600Ω Intrinsically Safe


# B5201

Provisional Data Sheet Nov. 01.

## Features

- 14.5mm Seated height
- Vacuum encapsulated
- Tested to 6.5kV DC isolation
- Fully shrouded connections
- Flammability to UL94 V0
- BASEFFA approvable

## Dimensions



Dimensions in mm

Connection pins require finished hole size of 1.0mm

Pin grid and box geometric centres coincide within a tolerance circle of 1.0mm

Tolerances  $\pm 0.1$ mm

## Technical Data

Parameter	Conditions	Value
Lp pins 1- 3	200Hz	>2.5H
Leakage Ls Pins 1- 3	10kHz	<9.5mH
Ratio Pins 1-3 : 4-6		1 : 1
DC Resistance		>35Ω per winding
Insertion Loss		<1.0db
Isolation Voltage	DC	Tested for 1 min @ 6.5kV
Operating range		Ambient Temperature
Functional		-10°C to +70°C
Storage		-40°C to +125°C

**Best**  
**Windings Ltd**

<http://www.bestwindings.co.uk/>

*Best Windings Ltd, Viking Works,  
7 Bucklesham Road, Kirton, Ipswich,  
Suffolk, England. IP10 0NX  
E-Mail: [sales@bestwindings.co.uk](mailto:sales@bestwindings.co.uk)  
Tel: + 44 (0) 1394 448 424  
Fax: + 44 (0) 1394 448 430*

©The product numbers used are the trademarks of Best Windings Ltd  
©1996 Best Windings Ltd. Reproduction Prohibited

May 1996