

Low profile line hold choke.

P1467

Features

- Industry Standard
- Low profile
- BS 6305 match compatible
- High reliability under adverse line transient conditions
- Permits balanced mode signalling

Application

- Telecommunications
- V.22 bis modems
- Line matching
- Instrumentation
- Fax/modems
- Portable computers

Description

P1467 is a choke designed for application to standard 600Ω PSTN line terminations in cases where the height available is limited, it has a split winding in order to permit balanced-mode signalling. It is intended for use with line transformer P1200 and has a low maximum seated height of only 14.6mm. Other transformers may be used but they may require different component values. The P1467 is designed with BS 6301 para. 4.4 in mind, which specifies certain overvoltage tests, and is therefore constructed using materials having adequate margins. Under conditions of very poor ventilation the overvoltage test causes a

winding temperature rise of 137°C. As well as this, balanced mode signalling carries risk of short-circuits from line to ground; protective measures may be needed to deal with this situation. Under normal worst-case conditions the rise is 100°C after 2 hours continuous line hold. Choke P1467 can easily be arranged to meet BS 6305 Class (a). In view of this there is no point in considering Class (b) further in these notes, although Class (b) can be met with a wide safety margin except for the restriction on modem line terminal impedance. P1467 is ideal in situations where lightning strikes make semiconductors vulnerable.

Specifications

Parameter	Conditions	Min	Typical	Max	Units
Insertion loss	N/A due to nature of terminations				
Frequency response	+3dB max tilt	200		4000	Hz
Return loss	200Hz - 4kHz	18			dB
Distortion	2nd & 3rd harmonic (DC 0 to 85mA)			70	dBm
Balance	DC - 5kHz Method TG25	80			dB
Shunt inductance	200 Hz -40dBm	0.8			H
Shunt loss R	200 Hz -40dBm	8			kΩ
DC resistance	20°C	185		200	Ω


Best
Windings Ltd

www.bestwindings.co.uk


*Best Windings Ltd, Viking Works,
Bucklesham Road, Kirton, Ipswich,
Suffolk, England. IP10 0NX
E-Mail: sales@bestwindings.co.uk
Tel: +44 (0) 1394 448 424
Fax: +44(0) 1394 448 430*

P1467

Dimensions



Connections



Information

Construction

Dimensions are shown in millimetres (inches).
Open frame having the core bonded by epoxy resin.

Absolute Maximum Ratings

(Ratings of components independent of circuit)

DC current

85mA (meets inductance claim)

DC current

100 mA (endurance)

Storage temperature

-40°C to $+125^{\circ}\text{C}$

Lead temperature, 10s

260°C

**Best
Windings Ltd**

www.bestwindings.co.uk

©2007 The product reference numbers used are the trademarks of Best Windings Ltd.

November 2007

Best Windings Ltd, Viking Works,
Bucklesham Road, Kirton, Ipswich,
Suffolk, England. IP10 0NX
E-Mail: sales@bestwindings.co.uk
Tel: +44 (0) 1394 448 424
Fax: +44(0) 1394 448 430